

PT60 Narvalo

Windows Mobile Computer



Features

- ◆ **Windows CE Operating System.**
Built to work with Windows CE, the PT60 Narvalo can support your technology environment perfectly.
- ◆ **Uninterrupted Productivity.**
Equipped with a 3,800 mAh battery, the PT60 Narvalo lasts an average of 10 hours. For scan intensive workdays, a cradle with spare battery charging slot can be used to ensure a full charge is always on hand.
- ◆ **Stay Connected.**
The PT60 Narvalo is equipped with WiFi (802.11b/g/n, 2.4 Ghz) that supports up to 54Mbps. Additionally, it is possible to communicate with other devices through Bluetooth.
- ◆ **Less Weight, more Comfort**
At only 303g (including battery), this mobile computer brings all day comfort to your operations. Its physical keyboard combined with a crystal clear 3.7 inch touch screen allows workers to navigate the device with ease.
- ◆ **Effortless out of the Box Experience.**
Take the PT60 Narvalo out of the box and get started right away. The device comes ready to use and configuration is quick and simple, minimizing the time needed to set up the devices.



Application Scenarios

Transport and Logistics (Warehouse, Backoffice), Retail (Warehouse, Backoffice, Store), Manufacturing (Operational Data Collection) and Healthcare (Patient Care, Laboratory and pharmacy).

PT60 Narvalo

Windows Mobile Computer

Performance	Processor	Marvell XScale PXA310, 806MHz CPU		
	Operating System	Microsoft Windows CE.NET 6.0		
	Memory		256MB RAM	
			128MB ROM	
		4GB flash memory for user storage		
	Interface	Micro USB 2.0, Battery charging over USB supported		
Physical	Dimensions	166(L) ×73(W) ×26(H) mm		
	Weight	303g (including battery)		
	Display	3.7" WVGA with backlight TFT touch screen		
	Keypad	33 keys (side keys included) with backlight		
	Notification	Vibrator, speaker and multi-color LEDs		
	Battery	Main	3.7V, 3800mAh rechargeable Li-Polymer battery	
		Backup	3.7V, 150mAh rechargeable Li-Polymer battery (supports 50-hour data backup)	
	Expected Battery Life	10 hours (1 scan per second)		
	Expansion	MicroSD card slot (max. 32GB)		
	AC Adapter	Output: DC5V, 1.5A Input: AC100~240V, 50~60Hz		
Environmental	Operating Temperature	-10°C to 50°C (-14°F to 122°F)		
	Storage Temperature	-20°C to 60°C (-4°F to 140°F)		
	Humidity	5% to 95% (non-condensing)		
	Static Discharge	±15 kV (Air discharge), ±8 kV (Direct discharge)		
	Drop	1.2m		
	Sealing	IP54		
Barcode Scanning	1D Barcode	Laser (≥4mil) CCD (≥4mil)	Code 128, EAN-13, EAN-8, Code 39, UPC-A, UPC-E, Codabar, Interleaved 2 of 5, ISBN/ISSN, Code 93, etc.	
	2D Barcode	CMOS(≥5mil)	All major 1D symbologies, PDF417, QR Code, Data Matrix, Maxicode, Aztec, etc.	
Wireless	WLAN RADIO	IEEE 802.11 b/g/n, security supports EAP, WEP, WPA, WPA2		
	WPAN RADIO	Bluetooth Class II V2.0		
Certifications	FCC Part15 Class B, CE EMC Class B, CCC			
Accessories	Cradle, battery, AC adapter, USB cable, stylus			

*Specifications are subject to change without notice.

Newland EMEA HQ
+31 (0) 345 87 00 33
info@newland-id.com

Newland D-A-CH
+49 (0) 6182 82916-16
info@newland-id.de

Newland France
+31 (0) 345 87 00 33
france@newland-id.com

Newland Benelux
+31 (0) 345 87 00 33
benelux@newland-id.com

Newland Ibérica
+34 (0) 93 303 74 66
info@newland-id.es

Newland Italy
+39 (0) 342 056 2227
italy@newland-id.com

Newland Nordic & Baltic
+46 (0) 708 847 767
nordic@newland-id.com

Newland UK
+44 (0) 1442 212 020
sales@newland-id.co.uk

Newland Russia
+31 (0) 345 87 00 33
russia@newland-id.com

Newland South Africa
+27 (0) 11 553 8010
info@newland-id.co.za

Newland Middle East
+31 (0) 345 87 00 33
middleeast@newland-id.com

Newland Turkey & Iran
+90 (0) 544 538 40 49
turkey@newland-id.com
iran@newland-id.com